



HYDROCLEAN


High pressure and misting

Hydrorock




SPECIFICATIONS

The latest generation of flexible hose, soft, light and very resistant, specially adapted for use in abrasive environments. It can withstand temperatures from -40°C to 100°C. The length of the hose varies between 10m and 35m. The hydrorock is 4 times more abrasion resistant and 2 times lighter than a hose.



4 fois plus résistant à l'abrasion



2 fois plus léger qu'un flexible standard

REFERENCES	SPECIFICATIONS	DIAMETER	LENGHT	PRESSURE
			m	Bar
101749S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	10	345
101750S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	15	345
101751S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	20	345
101752S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	25	345
101753S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	30	345
101754S	HYDROROCK 3/8 - FITTING : FBSP 3/8	10	35	345

Non contractual photo - 0922



Parc d'activités de Gohélève Sud - 56920 Noyal-Pontivy
Tél : 02 97 25 93 00 - Fax : 02 97 25 93 09
Email : contact@hydroclean-hp.fr - Site : www.hydroclean-hp.fr

Follow-us

