




HYDROCLEAN

Haute pression et brumisation



UHP



Non contractual photo - 0922

Specifications

- **Pump** : (radial) crankshaft 1450 rpm, 3 ceramic pistons
- **Motor** : three phase electric engine
- **Motor-pump coupling** : elastic flector coupling + protector
- **Electric cable** : 10m
- **Frame** : galvanized welded steel with wheelbarrow arms
- **Hood** : stainless steel
- **Wheels** : Pneumatic wheels tubeless Ø 400 mm
- **HP control circuit** : HP regulator with regulation valve integrated, safety valve and manometer

Options

- **Soft starter**
- **Time-delayed total stop**
- **Manual UHP hose reel**
- **UHP rotating nozzle**

Standard Equipment

- **Hose** : UHP 500 bar
- **HP gun** : UHP stainless steel
- **Single lance** : stainless steel reinforced UHP 900
- **Flat jet nozzle**
- **Easy removable couplings 600 bar**

REFERENCE	PRESSURE	FLOW		MOTOR		PUMP			WEIGHT
	Bar	l/min	l/h	CV	kW	Brand	Rpm	Oil	kg
NTHP400/20	400	20	1200	20	15	UDOR	1450	15W40	160
NTHP500/15	500	15	900	20	15	UDOR	1450	15W40	160



Parc d'activités de Gohélève Sud - 56920 Noyal-Pontivy
Tél : 02 97 25 93 00 - Fax : 02 97 25 93 09
Email : contact@hydroclean-hp.fr - Site : www.hydroclean-hp.fr

Follow us

